中国兵器工业集团 NORINCO GROUP

襄阳五二五泵业有限公司 XIANGYANG WUERWU PUMP INDUSTRY CO., LTD.

FYL 型磷酸料浆泵

FYL Phosphoric Acid Slurry Pump

电力、石油、化工

矿业、冶金、污水处理

造纸、船舶等其它行业

FYL 型磷酸料浆泵

产品简介
Brief Introduction

FYL 型液下泵为单级单吸离心式液下工作泵，用于输送萃取磷酸料浆 30~32%P2O5，温度 30~70℃，液固比 4:1~3:1, 亦可用于其他腐蚀介质或悬浮液的输送。

The FYL type sump pump is a single stage single suction centrifugal pump. It is widely used to transferring extracting phosphoric acid, slurry(contain of 30~32%P2O5, temperature at 30~70 ℃, liquid-solid ratio 2.5~3:1) and other corrosive medium or suspension.

技术参数
Technical Design

流量 Flow Rate:6.3 ~ 100m^3/h;
扬程 Head：12.5 ~ 35m;
温度 Temperature:-30 ~ +70℃;
压力等级 Pressure grade: PN2.5MPa;
应用：磷酸料浆 30 ~ 32% P2O5，其他腐蚀介质或悬浮液
Application: phosphoric acid pulp with 30 ~ 32% P2O5, other corrosive liquid or suspension;
材质：铬合金、镍钢、不锈钢、双相不锈钢、哈氏合金、各种合金钢
Material: Chromium alloy, nickel steel, stainless steel, duplex stainless steel, hastalloy, alloy steel.

FYL Phosphoric Acid Slurry Pump

通过调节轴向调整装置，调整叶轮和壳体的间隙，确保最优效率

Adjust the clearance between impeller and casing through the axial adjusting device to guarantee the beat efficiency.

FYL 型磷酸料浆泵

产品简介
Brief Introduction

FYL 型液下泵为单级单吸离心式液下工作泵，用于输送萃取磷酸料浆 30~32%P2O5，温度 30~70℃，液固比 4:1~3:1, 亦可用于其他腐蚀介质或悬浮液的输送。

The FYL type sump pump is a single stage single suction centrifugal pump. It is widely used to transferring extracting phosphoric acid, slurry(contain of 30~32%P2O5, temperature at 30~70 ℃, liquid-solid ratio 2.5~3:1) and other corrosive medium or suspension.

技术参数
Technical Design

流量 Flow Rate:6.3 ~ 100m^3/h;
扬程 Head：12.5 ~ 35m;
温度 Temperature:-30 ~ +70℃;
压力等级 Pressure grade: PN2.5MPa;
应用：磷酸料浆 30 ~ 32% P2O5，其他腐蚀介质或悬浮液
Application: phosphoric acid pulp with 30 ~ 32% P2O5, other corrosive liquid or suspension;
材质：铬合金、镍钢、不锈钢、双相不锈钢、哈氏合金、各种合金钢
Material: Chromium alloy, nickel steel, stainless steel, duplex stainless steel, hastalloy, alloy steel.

FYL Phosphoric Acid Slurry Pump

通过调节轴向调整装置，调整叶轮和壳体的间隙，确保最优效率

Adjust the clearance between impeller and casing through the axial adjusting device to guarantee the beat efficiency.

襄阳五二五泵业有限公司
中国湖北省襄阳市高新区日产工业园新光路 2 号
邮编：441004

市场 - 脱硫、化工	市场 - 矿山、冶金、石化	市场 - 海外、铸件
电话：0710-3566525	电话：0710-3722525	电话：+86-710-3563302
传真：0710-3560788	传真：0710-3560788	传真：+86-710-3560788

No.2 Xinguang Road, Hi-tech Zone,
Xiangyang City, Hubei Province, P.R. China
Post Code: 441004

Market-FGD/Chemicals	Market-Mine/Metallurgy/Petrochemicals	Market- Oversea/Casting
Tel:+86-710-3566525	Tel:+86-710-3722525	Tel:+86-710-3563302
Fax:+86-710-3560788	Fax:+86-710-3560788	Fax:+86-710-3560788